

coverSMART range Njala



Acrylic treated polyester polycotton.
Designed for awnings & outdoor structures.
Waterproof. UV resistant. Fungal Resistant.

Colours: Black

Width: 2m

PRODUCT WEIGHT	NJALA 330	NJALA 510
Weight (gsm)	330 ±5%	510 ±5%

PROPERTY		UNITS	METHOD	NJALA 330	NJALA 510
Tensile Strength	Warp	N / 5 cm	BS 13934-1	≥ 2,000	
Tensile Strength	Weft			≥ 1,200	≥ 1,600
Water Penetration		mm H2O	ISO 811-1981	≥ 800	≥ 600
Water Repellency		Rating	AATCC 22	≥ 90	
Colour Fastness to Light (I)		Rating	ISO 105-B04	≥ 7	
Abrasion Resistance (Textiles)		Cycles	ABRASION ASTM D4966-98	20,000	

BASE FABRIC PROPERTIES		NJALA 330	NJALA 510
Composition		Polycotton (75:25) Acrylic Coated	Polycotton (60:40) Acrylic Coated
Construction		Plain Weave	Plain Weave

cover**SMART** range

Njala



The information in this document is provided for general guidance only and does not serve as a warranty or guarantee of product performance or sustainability. It should not be interpreted as a Certificate of Conformance nor imply certification or compliance with any formal standards. All observations, recommendations, and predictions contained herein are estimations based on available data at the time of issue and are not binding. Actual results may vary due to operational conditions, specific processes, intended applications, environmental and climatic factors, pollution, force majeure, and other variables.

It is the responsibility of the customer or end-user to conduct field tests to verify the product's suitability for their intended purpose. Smart Ikhaya disclaims any liability for damages or losses arising from reliance on the information in this document. Our standard terms and conditions apply to all products sold.