

# coverSMART range

## Tonneau Standard



Woven Polyester. Designed for Tonneau Covers for Automotive OEM and aftermarket.

Colours: Black

Width: 1.85 m

PRODUCT WEIGHT	
Overall Mass	570 g/m2 [BS3424.4] (±20%)

PRODUCT PROPERTIES		UNIT	METHOD	TOLERANCE	VALUE
Tensile	WMD	N / 50mm	BS 3424:4 Method 6	min.	2,200
	AMD			min.	1,800
Tear	WMD	N	BS 3424:5 Method 7C	min.	150
	AMD			min.	200
Coating Adhesion		N / 25 mm	BS 3424:9 Method 9B	min.	35
Fusion of PVC		No Disintegration	BS 3424:22	min.	OK
Resistance to Flexions		250,000	BS 3424:9 Method 11C	No Cracks	5

BASE FABRIC PROPERTIES	
Composition	Woven Polyester

# coverSMART range

## Tonneau Standard



The information in this document is provided for general guidance only and does not serve as a warranty or guarantee of product performance or sustainability. It should not be interpreted as a Certificate of Conformance nor imply certification or compliance with any formal standards. All observations, recommendations, and predictions contained herein are estimations based on available data at the time of issue and are not binding. Actual results may vary due to operational conditions, specific processes, intended applications, environmental and climatic factors, pollution, force majeure, and other variables.

It is the responsibility of the customer or end-user to conduct field tests to verify the product's suitability for their intended purpose. Smart Ikhaya disclaims any liability for damages or losses arising from reliance on the information in this document. Our standard terms and conditions apply to all products sold.