

# ripSMART range RIPSTOP



**Acrylic treated polyester fabric to withstand the harsh African environment. Designed for outdoors tenting, awnings & outdoor structures. UV Protection. Fungal Resistant. Waterproof.**

**Colours:** Multiple colours

**Width:** 1.8 m

PROPERTY	UNITS	METHOD	300	400	500
Composition			PES/Acrylic	PES/Acrylic	PES/Acrylic
Construction			Woven	Woven	Woven
Coated Weight	gsm	ISO 3801	330 ±5%	400 ±5%	500 ±5%
Width	mm	Supplier	1800	1800	1800
Tensile Strength	N	ISO 13934 -1:1999	Warp > 2,000 Weft > 1,000	Warp > 2,000 Weft > 1,000	Warp > 2,000 Weft > 2,000
		ISO 13937-2:2000	Warp >70 Weft > 50	Warp >100 Weft > 120	Warp >180 Weft > 200
Water Penetration	mm/H2O	ISO 811	> 1,000	> 1,000	> 1,000
Colour fastness to light	Blue Scale	ISO 105-804	≥ 4	≥ 4	≥ 4
Colour fastness to rubbing	Grey Scale	ISO 105-X12	≥ 4	≥ 4	≥ 4
Fungal Resistance		AC M/L 13	Pass	Pass	Pass

# ripSMART range

## RIPSTOP



The information in this document is provided for general guidance only and does not serve as a warranty or guarantee of product performance or sustainability. It should not be interpreted as a Certificate of Conformance nor imply certification or compliance with any formal standards. All observations, recommendations, and predictions contained herein are estimations based on available data at the time of issue and are not binding. Actual results may vary due to operational conditions, specific processes, intended applications, environmental and climatic factors, pollution, force majeure, and other variables.

It is the responsibility of the customer or end-user to conduct field tests to verify the product's suitability for their intended purpose. Smart Ikhaya disclaims any liability for damages or losses arising from reliance on the information in this document. Our standard terms and conditions apply to all products sold.