

tarpSMART range

Tarpaulin 800gsm Local



High tenacity Polyester yarn coated on both sides with thick PVC to enhance durability. Plain Weave. This material possesses higher mechanical tear and wear properties. Designed for heavy duty tarpaulin and side curtains.

Colours: Multiple colours

Width: 3 m

PRODUCT PROPERTIES		UNIT	METHOD	VALUE
Tensile	WMD	N / 50mm	BS 3424 Part 4 Method 6	3,200
	AMD			2,800
Tear	WMD	N	BS 3424 Part 5 Method 7 c	800
	AMD			600
Weld tear strength		N / 50mm	BS 3424:22	80
Fusion	Acetone	min	BS 3424:22	5
	Ethyl Acetate	min		10
Flex Cracking		Cycles	SABS 411	250,000

BASE FABRIC PROPERTIES	
Composition	100 % Polyester
Fabric mass per unit area	min. 230 [SANS79]
Linear Density (Warp)	1,100 d/d Tex [BS 3424]
Linear Density (Waft)	1,100 d/d Tex [BS 3424]
Overall Mass	800 g/m2 [BS3424.5] (±20%)

tarpSMART range

Tarpaulin 800



The information in this document is provided for general guidance only and does not serve as a warranty or guarantee of product performance or sustainability. It should not be interpreted as a Certificate of Conformance nor imply certification or compliance with any formal standards. All observations, recommendations, and predictions contained herein are estimations based on available data at the time of issue and are not binding. Actual results may vary due to operational conditions, specific processes, intended applications, environmental and climatic factors, pollution, force majeure, and other variables.

It is the responsibility of the customer or end-user to conduct field tests to verify the product's suitability for their intended purpose. Smart Ikhaya disclaims any liability for damages or losses arising from reliance on the information in this document. Our standard terms and conditions apply to all products sold.