

# tarpsSMART range

## Clear PVC 750 Micron Standard



Designed for applications where visibility, durability and protection are key.

**Colours:** Clear

**Width:** 1.5 m

PRODUCT PROPERTIES	UNIT	METHOD	AVG VALUE	SPECIFICATION
<b>Tensile Strength</b>	MPA	AS2324-2.7	23.35	Speed 200mm/min
<b>Elongation at break</b>	%	AS 2324-2.9 Method A	338.50	Speed 200mm/min
<b>Heat Shrinkage</b>	%	80 10 min	1	
<b>Cold Resistance</b>	°C		-20	
<b>PHR</b>			42	
<b>Thickness</b>	mm		0.75	0.38-0.42

# tarpSMART range

## Clear PVC 750 Micron

## Standard



The information in this document is provided for general guidance only and does not serve as a warranty or guarantee of product performance or sustainability. It should not be interpreted as a Certificate of Conformance nor imply certification or compliance with any formal standards. All observations, recommendations, and predictions contained herein are estimations based on available data at the time of issue and are not binding. Actual results may vary due to operational conditions, specific processes, intended applications, environmental and climatic factors, pollution, force majeure, and other variables.

It is the responsibility of the customer or end-user to conduct field tests to verify the product's suitability for their intended purpose. Smart Ikhaya disclaims any liability for damages or losses arising from reliance on the information in this document. Our standard terms and conditions apply to all products sold.