

tarpsSMART range

Crysal Clear PVC 400

Micron Elite



Made specifically for outside weather conditions. Ideal for the manufacture of flexible windows for a large variety of applications such as: tents, awnings and canopies for the caravan industry, large marquees, weather protection for terraces, sprayhoods for boats, and even for industrial rolling doors.

Colours: Clear

Width: 1.4 m

PRODUCT WEIGHT	
Overall Mass Per 60m Roll	500 g/m ²
Surface weight	496 g/m ²

PRODUCT PROPERTIES	UNIT	SPECIFICATION	AVG VALUE
Thickness	Micron	EN2286 - 3 (10mm * 50 kPa)	400 +/- 5%
Density	g/m ³		1.25
Flexibility	PHR	-	46
Temperature Resistance	°C		-10 - +70
Shrinkage Average	%		<3
UV Resistance	Blue Scale		>5

tarpSMART range

Crysal Clear PVC 400

Micron Elite



PRODUCT PROPERTIES	UNIT	SPECIFICATION	AVG VALUE
Tensile Strength	N / mm ²	ASTM D882-02	M.D. 27.4
			T.D. 23.6
Elongation at break	%	ASTM D882-02	M.D. 275.8
			T.D. 288.4
Dimensional Stability	%	ASTM D1204-05 (10 min / 800 °C)	</3
		ASTM D1204-05 (10 min / 500 °C)	1.5
Weather Resistance		ASTM D1499 (Xenotest: 2 000 hrs)	Pass
Brittleness Temperature	°C	EN 1876-2 and ASTM D179-02	-20

M.D. = Longitudinal Direction T.D. = Transverse Direction.
 Light Transmission up to 92%
 Low shrinkage at room temperature < 1%

The information in this document is provided for general guidance only and does not serve as a warranty or guarantee of product performance or sustainability. It should not be interpreted as a Certificate of Conformance nor imply certification or compliance with any formal standards. All observations, recommendations, and predictions contained herein are estimations based on available data at the time of issue and are not binding. Actual results may vary due to operational conditions, specific processes, intended applications, environmental and climatic factors, pollution, force majeure, and other variables.

It is the responsibility of the customer or end-user to conduct field tests to verify the product's suitability for their intended purpose. Smart Ikhaya disclaims any liability for damages or losses arising from reliance on the information in this document. Our standard terms and conditions apply to all products sold.